






Professional Grade Duct Tape



Backing: PE Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Silver, Black, White, Blue, Brown, Green

OD, Red, Tan, Yellow

Specifications: Tested in accordance with UL 723

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Hanging and patching polyethylene sheeting
- Duct sealing and HVAC contractor uses
- Maintenance applications in manufacturing environments
- Sealing polyethylene waste disposal bags
- Color Coding
- General repair
- · Bundling, patching, and mending

Features

Benefits

- PE-Coated Cloth Backing
- Natural rubber based adhesive
- Low VOC Content

- Excellent balance of tensile strength and tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED*

Physical Properties

	Standard UOM	Metric UOM	Test Method	
Total Thickness	11 mils	279.4 mic	ASTM D-1000	
Adhesion to Steel	47 oz/in	5.14 N/cm	PSTC-101	
Tensile Strength	27 lb/in	47.28 N/cm	ASTM D-1000	
Operating Temperature	40-200°F	4-93°C		
Smoke Developed	5		UL 723	
Flame Spread	5		UL 723	
VOC Content	<1 g/L			

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 00081) by qualified technical personnel. To Berry Plastics' Innovietge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complex with all applicable feederal, state and local laws and regulations. The data are typical values submitted only for the user's information and considerable, and do not constitute a warranty of any kind (including but not limited to a warranty of menchantability or of fitness for a particular purpose), or a representation for which BERY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com Nijverheidsstraat 10 2260 Oevel (Westerlo) Belgium 32-014-722500 Fax 32-014-722570 4/21/2011