PRO Tape & Specialties

PRO CITRUS CLEANER PRODUCT DATA

DESCRIPTION: PRO CITRUS CLEANER NATURAL CITRUS CLEANER is formulated to use as a degreaser and adhesive remover on most substrates. **PRO CITRUS CLEANER** can be used safely on most surfaces. It is noncorrosive, has a pleasant citrus scent, removes adhesives, oil stains, road tar, rubber marks, decals, stickers, heel marks, graffiti, lipstick, release agents, soap films and degreases equipment. Compatibility with some plastics is of concern and testing on all substrates in typical operating environments is recommended to determine compatibility and suitability for use. **PRO CITRUS CLEANER** is recommended for use where chlorinated solvents cannot be used.

COMMON USE: Natural Citrus Cleaner

CONTAINER SIZE: 16 Fluid Ounce, (453.5g)

ODOR: Pleasant Citrus Scent

FLAMMABILITY: Extremely Flammable

USE ON PLASTIC SURFACES: Test on all substrates in typical operating environments is recommended to determine compatibility and suitability for use

CONTAINS ODC'S (OZONE DEPLETING CHEMICALS) No

PHYSICAL AND CHEMICAL RESISTANCE: This natural product is most effective and rinses off with water

SHELF LIFE: One year from date of shipment

APPLICATION, USES AND SUGGESTIONS: Shake well before using. Hold can 8 to 12 inches away from surface to be cleaned. Depress spray tip (with arrow pointed away from body) and, depending on difficulty, spray liberally and let the product work before rag wiping or rinsing with water. In difficult cleaning applications use a second application. Compatibility with some plastics is of concern and testing on all substrates in typical operating environments is recommended to determine compatibility and suitability for use. Read precautions on label before using.

PRO Tape & Specialties
Raritan Center • 100 Northfield Ave. • Edison, NJ 08837
800-345-0234

Inasmuch as PRO Tape & Specialties has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.